

Specification  
for  
General purpose AC Servo  
Power supply cable  
  
Type SC-PWC501C□M-XL

MITSUBISHI ELECTRIC  
SYSTEM & SERVICE CO.,LTD

Note

Revision								Drawn	Check	Design	Approved
								N.Ito	S.Kariya	T.Kasahara	D.Fukushima
Send to								Date		Dwg	
								7 Sep.,2022		X953503D70003-E98	
								Order			

## 1. SCOPE

This specification covers the requirements for the General purpose AC Servo Power supply cable.

• SC-PWC501C□M-XL

※ The Products covered in this specification don't include the toxic substances in RoHS.

※ UL's Wiring Harnesses Traceability program provides traceability for this cable.

## 2. CABLE TYPE

SC - PWC5 01 C □ M - XL

				Sign	Wire thickness / Bending life
				XL	Extra thick / Standard (For fixed part)
				Sign	Length of cable
				□	Refer to clause 4
				Sign	Connector specifications
				01	Screw tightening plug
				Sign	Application
				PWC5	Power supply cable

## 3. APPLICABLE STANDARDS

Wire part : UL standard (UL 758 : AWM)

UL Style No.	Rated	
2586	105°C	600V

#### 4. APPLICABLE SERVO MOTOR / LENGTH OF CABLE

1 to 100m

※ The maximum cable length differs depending on the motor.

Refer to the CABLE LENGTH SELECTION TABLE "R9535021-018028-010"  
for more information.

Refer to the CABLE SELECTION TABLE "R9535021-018028-015" for applicable motors.

#### 5. EXAMPLE OF PRINTING CABLE TYPE NAME

SC-PWC501C□M-XL    xxxxxxxx

※ □ is a figure from 1 to 100.


※ xxxxxxxx are the serial number for seven digits.

## 6. STRUCTURE AND CHARACTERISTICS

Item		Unit	Specification
Wire			
Structure		—	AWG8×4C
Conductor	Conductor size	—	AWG8
	Outer diameter	mm	Approx.4.5
Insulation	Material	—	PVC
	Outer diameter	mm	Approx.7.3
Twisted	Number of insulated core wire	—	4C
Sheath	Material	—	Flame resisting PVC
	color	—	Black
Overall diameter		mm	Approx. 21.3
Cable weight		kg/km	670
Electrical characteristics	Insulation resistance	MΩ・km	Over 10
	Withstand voltage	V / for 5 min	AC2000
Minimum bend radius		mm	6 times the overall diameter
Flame retardant		—	UL1581 VW-1
Connector			
Amplifier side		—	
Motor side	Type	Japan Aviation Electronics Industry, Ltd. JL04V-6A22-22SE-R (Straight plug) SANKEI MANUFACTURING CO.LTD, C2KD2422 (KEIGLAND Type C2)	
	IP rating	IP67*1	
Cable harness			
Environment	Ambient temperature	℃	0 to 60 (Without freezing)
	Ambient humidity	%RH	5 to 95 (Without condensation)
	Ambience	—	Indoors (no direct sunlight), no corrosive gas, inflammable gas, oil mist, or dust
Electrical characteristics	Insulation resistance	MΩ・km	Over 10
	Withstand voltage	V/for 1 min	AC2000


\*1 The IP rating indicated is for the connector's protection against ingress of dust and water when coupled to a servo amplifier/servo motor. If the IP rating of the servo amplifier/servo motor differs from that of these connectors, overall IP rating depends on the lowest of all.

## 7. STRUCTURAL DRAWING



## 8. OUTLINE DRAWING

[Unit : mm]



Refer to the following table for mark label and insulation color.

Mark label	Insulation color
U	Red
V	White
W	Black
E	Green / Yellow